



Northwest Adhesives, Inc.
6013 NE 127th Avenue
Vancouver, WA 98682

Phone: (360)-260-1227

FAX: (360)-260-1872

www.northwestadhesives.com

email: sales@northwestadhesives.com

Technical Information

Revised: 1-07

Description : A-036 "Cool Melt" is premium, low viscosity case and carton sealing adhesive blended from synthetic resins, polymers, wax & thermal stabilizers

The operating benefits of using A-036 can be:

safer for operators, uses less energy

lower price vs. other 250F melts

easier on melt equipment

less maintenance

faster warm up

lower odor

no char

"A" series products give dependable performance and are produced by a modern manufacturing process and a dedicated quality assurance program.

Solids:	100%
Form:	clear pellets
Color	v. light straw
Bulk Density:	5 lbs / gal
Application Temp:	250-275°F*
Viscosity (typical):	1800 cps @ 250°F 1200 cps @ 275°F
R&B Softening Range:	190°F

Packaging : A-036 "Cool Melt" hotmelt is packaged in heavy duty, corrugated boxes containing (50) lbs. There are (18) or (36) boxes stretch wrapped on a wood pallet.

*** Note: for fast set time and to get higher mileage run @ 250°F
for faster melting and for more open time, run @ 275°F**

Important: Consult Material Safety Data Sheet prior to using this product.

The product contained herein meets all specifications established and in effect on the date of manufacture.
No other warranty is expressed nor implied, nor are costs for damages incurred by its use available from the manufacturer beyond the cost of the product itself.
It is the sole responsibility of the purchaser to determine its suitability in their intended application.