



Northwest Adhesives, Inc.
6013 NE 127th Avenue
Vancouver, WA 98682

Phone: (360)-260-1227

FAX: (360)-260-1872

www.northwestadhesives.com

email: sales@northwestadhesives.com

Technical Information

effective 11/04

Description and Use: A-37 "Spot Wheel" is a low viscosity palletizing, self-tacking hotmelt adhesive blended from synthetic resins, oils, waxes and thermal stabilizers.

A-37 can be applied by nozzle or spot wheel onto the topside of corrugated boxes, folding cartons or multi-wall bags for pallet stabilization, reduced transit damage, higher stacking or reduced quantity of stretch film.

This formula matches closely current products used widely for beverage cartons by reducing the paper tearing when unstacked. The end user should test this product thoroughly at the highest temperature and highest stacking pressures encountered in their shipping and storage system to insure it meets all requirements.

Application Temp	250-275°F
Color	light amber
Form	1 lb "bricks"
Viscosity @ 350°F:	200 cps
Softening Pt:	180°F

(Note: increased or reduced tack can be adjusted by using more or less quantity and/or by changing the pattern)

Packaging and Form: A-37 hotmelt is packaged in heavy duty corrugated boxes containing 25 lbs x (36) boxes = 900 lbs / pallet. The anti-blocking powder disappears into the hot liquid as each brick is melted in the applicator tank.

Important: Consult Material Safety Data Sheet prior to using this product.

The product contained herein meets all specifications established and in effect on the date of manufacture. No other warranty is expressed or implied, nor are additional remedies for costs or damages incurred by its use available from the manufacturer beyond the cost of the product itself. It is the sole responsibility of the purchaser to test this product and determine its suitability in their intended application