



**Northwest Adhesives, Inc.**  
6013 NE 127th Avenue  
Vancouver, WA 98682

Phone: (360)-260-1227

FAX: (360)-260-1872

[www.northwestadhesives.com](http://www.northwestadhesives.com)

email: [sales@northwestadhesives.com](mailto:sales@northwestadhesives.com)

## Technical Information

effective 7/07

**Description and Use:** A-490 "Wood Label" is an economical pre-labeling hotmelt adhesive blended from synthetic resin, EVA polymer, wax and thermal stabilizers.

A-490 is applied hot to the end grain of dry lumber as a primer for the subsequent application of UPC bar code labels. A long open time provides improved adhesion. Low viscosity permits cleaner, less stringy application compared to HMPSA's.

Application Temp	300-320°F
Color	light amber
Form	free flowing "pellets"
Viscosity @ 350°F:	600 cps
Softening Pt:	180°F
Speed of set	very slow

**Packaging and Form:** A-490 "Wood Label" hotmelt is packaged in heavy duty corrugated boxes containing 50 lbs x (36) boxes = 1800 lbs / pallet.

Important: Consult Material Safety Data Sheet prior to using this product.

The product contained herein meets all specifications established and in effect on the date of manufacture. No other warranty is expressed or implied, nor are additional remedies for costs or damages incurred by its use available from the manufacturer beyond the cost of the product itself. It is the sole responsibility of the purchaser to test this product and determine its suitability in their intended application