



Northwest Adhesives, Inc.

5913 NE 127th Avenue, Suite 700

Vancouver, WA 98682

Phone: (360)-260-1227

Fax: (360)-260-1872

Email: adhesive@pacifier.com

Technical Information

effective 10/05

Description and Use: A-95 is an aggressive, pressure sensitive palletizing hotmelt applied in spots to the topside of corrugated boxes for transit stabilization.

A-95 can reduce use of expensive stretch film*
Permanent tackiness allows for delayed stacking
Re-stacking of pallets is possible

Application Temp	275°F
Viscosity:	500 cps @ 350°F
Softening Pt.	160°F

Packaging and Form: A-95 "Palletizing" is available in 24 ~ 1# bricks (3 x 3 x 3) shipped in silicone liners, packed 24 per "pour and ship" pack. There are (36) packs x 25 lbs = 900 lbs per pallet S/W on wood skid.

*Note, boxes need to be overlapped not column stacked to eliminate completely the use of stretch film but if boxes are column stacked, 50% less film can be used.

Important: Consult Material Safety Data Sheet prior to using this product.

The product contained herein meets all specifications established and in effect on the date of manufacture. No other warranty is expressed nor implied, nor are costs for damages incurred by its use available from the manufacturer beyond the cost of the product itself. It is the sole responsibility of the purchaser to determine its suitability in their intended application.